

Series GC

WHEEL



They are made of a plastic material center and a coat in puncture proof foam material

They are used for the transport of loads on uneven floors, ensuring maximum protection against shock and vibration

WHEEL FEATURES

PLAIN BORE (PB)	ROLLER BEARING (RB)	DIAMETER	TYRE WIDTH	HUB WIDTH	BORE DIAMETER	OPERATING TEMPERATURE
GC200PB	GC200RB	200	50	58	20	-20 +60

HOUSINGS



GALVANISED STEEL PLATE BRACKET

FIXED		PLATE	PLATE + BRAKE		CAP		CAP + BRAKE										
SM200F001. GC200PB	SM200F001. GC200RB	SM200GP01. GC200PB	SM200GP01. GC200RB	SM200GPB1. GC200PB	SM200GPB1. GC200RB	SM200GC01. GC200PB	SM200GC01. GC200RB	SM200GCB1. GC200PB	SM200GCB1. GC200RB	200mm	140x110mm	105x80mm	11mm	12mm	238mm	60mm	75

STAINLESS STEEL PLATE BRACKET

FIXED		PLATE	PLATE + BRAKE		CAP		CAP + BRAKE										
SM200F005. GC200PB	SM200F005. GC200RB	SM200GP05. GC200PB	SM200GP05. GC200RB	SM200GPB5. GC200PB	SM200GPB5. GC200RB	SM200GC05. GC200PB	SM200GC05. GC200RB	SM200GCB5. GC200PB	SM200GCB5. GC200RB	200mm	140x110mm	105x80mm	11mm	12mm	238mm	60mm	75