

Series NE

WHEEL



Made of high-viscosity nylon 6, these wheels have excellent resistance to wear, abrasion and impact

They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocar-bons

It should be noted that above + 30 ° the load capacity is reduced








WHEEL FEATURES

PLAIN BORE (PB)	ROLLER BEARING (RB)	INOX ROLLER BEARING (IB)	DIAMETER	TYRE WIDTH	HUB WIDTH	BORE DIAMETER	OPERATING TEMPERATURE
NE125PB			125	35	44	20	-25 +80
NE200PB	NE200RB	NE200IB	200	50	58	20	-25 +80








HOUSINGS



GALVANISED STEEL PLATE BRACKET

FIXED		PLATE		PLATE + BRAKE		CAP		CAP + BRAKE									
SM125F001. NE125PB		SM125GP01. NE125PB		SM125GPB1. NE125PB		SM125GC01. NE125PB		SM125GCB1. NE125PB		125mm	100x85mm	80x60mm	9mm	12mm	156mm	45mm	180
SM200F001. NE200PB	SM200F001. NE200RB	SM200GP01. NE200PB	SM200GP01. NE200RB	SM200GPB1. NE200PB	SM200GPB1. NE200RB	SM200GC01. NE200PB	SM200GC01. NE200RB	SM200GCB1. NE200PB	SM200GCB1. NE200RB	200mm	140x110mm	105x80mm	11mm	12mm	238mm	60mm	300

STAINLESS STEEL PLATE BRACKET

FIXED		PLATE		PLATE + BRAKE		CAP		CAP + BRAKE									
SM125F005. NE125PB		SM125GP05. NE125PB		SM125GPB5. NE125PB		SM125GC05. NE125PB		SM125GCB5. NE125PB		125mm	100x85mm	80x60mm	9mm	12mm	156mm	45mm	180
SM200F005. NE200PB	SM200F005. NE200IB	SM200GP05. NE200PB	SM200GP05. NE200IB	SM200GPB5. NE200PB	SM200GPB5. NE200IB	SM200GC05. NE200PB	SM200GC05. NE200IB	SM200GCB5. NE200PB	SM200GCB5. NE200IB	200mm	140x110mm	105x80mm	11mm	12mm	238mm	60mm	300