

Series PD

WHEEL



Made of a nylon 6 core and a coating of thermoplastic polyurethane, these wheels ensure a complete protection of floors and a total absence of noise while using a tread of relatively high hardness (98 Shore A)

They have excellent resistance to abrasion, mineral oils and greases

May have limitations for use in the presence of water vapor

WHEEL FEATURES

BALL BEARING (BB)	DIAMETER	TYRE WIDTH	HUB WIDTH	BORE DIAMETER	OPERATING TEMPERATURE
PD80BB	80	34	40	12	-20 +60
PD125BB	125	40	44	15	-20 +60
PD160BB	160	45	58	20	-20 +60
PD200BB	200	45	58	20	-20 +60

HOUSINGS



GALVANISED STEEL PLATE BRACKET

FIXED	PLATE	PLATE + BRAKE	CAP	CAP + BRAKE									
SM080F001. PD80BB	SM080GP01. PD80BB	SM080GPB1. PD80BB	SM080GC01. PD80BB	SM080GCB1. PD80BB	80mm	105x80mm	80x60mm	9mm	10mm	108mm	42mm	100	
SM125F001. PD125BB	SM125GP01. PD125BB	SM125GPB1. PD125BB	SM125GC01. PD125BB	SM125GCB1. PD125BB	125mm	100x85mm	80x60mm	9mm	12mm	156mm	45mm	180	
SM160F001. PD160BB	SM160GP01. PD160BB	SM160GPB1. PD160BB	SM160GC01. PD160BB	SM160GCB1. PD160BB	160mm	140x110mm	105x80mm	11mm	12mm	198mm	45mm	300	
SM200F001. PD200BB	SM200GP01. PD200BB	SM200GPB1. PD200BB	SM200GC01. PD200BB	SM200GCB1. PD200BB	200mm	140x110mm	105x80mm	11mm	12mm	238mm	60mm	300	

STAINLESS STEEL PLATE BRACKET

FIXED	PLATE	PLATE + BRAKE	CAP	CAP + BRAKE									
SM080F005. PD80BB	SM080GP05. PD80BB	SM080GPB5. PD80BB	SM080GC05. PD80BB	SM080GCB5. PD80BB	80mm	105x80mm	80x60mm	9mm	10mm	108mm	42mm	100	
SM125F005. PD125BB	SM125GP05. PD125BB	SM125GPB5. PD125BB	SM125GC05. PD125BB	SM125GCB5. PD125BB	125mm	100x85mm	80x60mm	9mm	12mm	156mm	45mm	180	
SM160F005. PD160BB	SM160GP05. PD160BB	SM160GPB5. PD160BB	SM160GC05. PD160BB	SM160GCB5. PD160BB	160mm	140x110mm	105x80mm	11mm	12mm	198mm	45mm	300	
SM200F005. PD200BB	SM200GP05. PD200BB	SM200GPB5. PD200BB	SM200GC05. PD200BB	SM200GCB5. PD200BB	200mm	140x110mm	105x80mm	11mm	12mm	238mm	60mm	300	