Series PF

WHEEL



Made of a nylon 6 core and a coating of elastic injected polyurethane, these wheels ensure a complete protection of floors and a total absence of noise thanks to a tread hardness of 82 Shore A

They have an excellent elastic behavior which can guarantee a better shock absorption and vibration

They have a high resistance to abrasion, mineral oils and greases

These wheels are also available with a white core and blue coating

WHEEL FEATURES

BALL BEARING (BB)	DIAMETER	TYRE WIDTH	HUB WIDTH	BORE DIAMETER	OPERATING TEMPERATURE
PF80BB	80	30	40	8	-20 +60
PF100BB	100	30	40	8	-20 +60
PF125BB	125	35	45	8	-20 +60

HOUSINGS











GALVANISED STEEL PLATE BRACKET

FIXED	PLATE	PLATE + BRAKE	CAP	CAP + BRAKE	<u></u>		Þ; ;4 ⊕ .₽ □ .□		J	<u>.</u>		
SM080F001. PF80BB	SM080GP01. PF80BB	SM080GPB1. PF80BB	SM080GC01. PF80BB	SM080GCB1. PF80BB	80mm	105x80mm	80x60mm	9mm	10mm	108mm	42mm	100
SM100F001. PF100BB	SM100GP01. PF100BB	SM100GPB1. PF100BB	SM100GC01. PF100BB	SM100GCB1. PF100BB	100mm	105x80mm	80x60mm	9mm	10mm	128mm	42mm	120
SM125F001. PF125BB	SM125GP01. PF125BB	SM125GPB1. PF125BB	SM125GC01. PF125BB	SM125GCB1. PF125BB	125mm	100x85mm	80x60mm	9mm	12mm	156mm	45mm	130

STAINLESS STEEL PLATE BRACKET

FIXED	PLATE	PLATE + BRAKE	CAP	CAP + BRAKE	<u>(</u>		₩ .₩ ₩ .₩		Ī	<u>.</u>		
SM080F005. PF80BB	SM080GP05. PF80BB	SM080GPB5. PF80BB	SM080GC05. PF80BB	SM080GCB5. PF80BB	80mm	105x80mm	80x60mm	9mm	10mm	108mm	42mm	100
SM100F005. PF100BB	SM100GP05. PF100BB	SM100GPB5. PF100BB	SM100GC05. PF100BB	SM100GCB5. PF100BB	100mm	105x80mm	80x60mm	9mm	10mm	128mm	42mm	120
SM125F005. PF125BB	SM125GP05. PF125BB	SM125GPB5. PF125BB	SM125GC05. PF125BB	SM125GCB5. PF125BB	125mm	100x85mm	80x60mm	9mm	12mm	156mm	45mm	130

56 | Albertini Ruote | medium duty